

Dualoy[®] 3000/LCX: Installs Fast. Proven to Last.

Revolutionary coaxial fiberglass piping system provides long service life without long installation time.

Introducing Dualoy 3000/LCX, the first coaxial rigid fiberglass piping system for service station installations. The unique advantage of Dualoy 3000/LCX is that an experienced fiberglass pipe installer can put in a coaxial fiberglass system *in virtually the same time* as single wall fiberglass.

The secondary and primary pipe form an integral unit with a small interstitial space. The time required to cut, join and test the system is dramatically reduced without sacrificing the integrity of the double-containment system.

With Dualoy 3000/LCX, expect the proven quality, performance and reliability of Ameron's UL Listed Dualoy 3000/L rigid fiberglass piping line: secure containment of petroleum products, alcohols and alcohol-gasoline blended fuels and excellent flow characteristics.

Dualoy 3000/LCX gets the service station in operation faster with a secondary containment system that is proven to last.

- Ameron's exclusive mechanical closure for secondary containment joint speeds installation time, reducing down time.
- Unique, proprietary pre-fabricated fittings maintain continuity of the interstitial space and eliminate the need for special containment fasteners.
- Small interstitial space in the coaxial design affords faster leak detection.
- Inherent strength of fiberglass allows for higher test pressures and maximum operating pressures.
- Maintains constant slope from tank to dispenser.
- Breakthrough double wall design of Dualoy 3000/LCX offers greater damage resistance during shipping and installation.

Fiberglass Pipe Group

5300 Hollister • Suite 111 • Houston, Texas 77040
(713)690-7777 • Fax (713)690-2842 • www.ameron.com

